Journal of Innovative Technology, Vol. 8, No. 2, pp. 59-68, September 2026
http://doi.org/10.29424/JIT.202609_8(2).0006

Hydrological and Energy Perspectives of Run-of-River Hydropower: A Physics-Based Approach to Sustainable Water Resource Utilization

Naveed Ahmed Malik [1], Babar Sattar Khan [2], Naveed Ishtiaq Chaudhary [3*]

ABSTRACT

Run-of-river (RoR) hydropower systems offer an eco-friendly alternative to conventional dam-based energy generation by harnessing river flow without large-scale water impoundment. This study explores RoR as a sustainable approach to decentralized energy generation while maintaining the integrity of natural water systems. Using the principles of classical mechanics, we analyze how the kinetic energy and potential energy in flowing water can be effectively converted into electricity with minimal disruption to the river's hydrological regime. A case study from Northern Pakistan is presented, where a 1 MW RoR plant operates in a glacial-fed river basin. The study assesses the system's impact on flow continuity, local water use, and aquatic ecosystem balance. Visual data, energy-flow models, and hydrological assessments illustrate the dual role of RoR systems in water resource utilization and renewable energy supply. Our study supports the integration of RoR hydropower within broader water management strategies, especially in semi-arid and mountainous regions, offering benefits such as year-round electricity, reduced evaporation losses, and preservation of downstream water availability. Interdisciplinary insight is fostered at the intersection of applied water science and sustainable development, encouraging policymakers to consider RoR in environmentally sensitive hydropower planning.

Keywords: Chitral hydropower project; classical mechanics; energy systems; hydel power generation; kinetic energy; potential energy; run-of-river; sustainable energy.

1. INTRODUCTION

Water is the cornerstone of all life, playing a critical role in health, agriculture, industry, and energy systems. As global populations grow and freshwater sources are becoming depleted, the sustainable use of water has become more essential. At the same time, reducing carbon emissions and environmental degradation requires a shift toward renewable and eco-friendly energy solutions. Among these, RoR hydropower stands out as a clean energy approach that also preserves the continuity of natural river flows. Unlike large dams, RoR systems generate electricity with minimal water storage and reduced ecological disruption, offering a balance between energy needs and water resource protection. A map illustrating the potential for RoR hydropower in small basins for sustainable energy is presented in research [1], and it closely matched the electrical output and spatial distribution of hydropower units that are in operation. Additionally, it is shown that the hydropower potential map accurately depicts the hydropower advancements that correlate to Japan's electric power systems history, demonstrating its excellent dependability. RoR hydropower plants have no effect on the water quality index (WQI) and hydro-chemical dynamics, according to research on the Sindh River in the Kashmir Himalayas that was published in [2]. This emphasizes the significance of thorough evaluations for sustainable RoR development. The findings imply that the WQI value was not considerably increased by diverting water for RoR operation to the extent that the water in the bypassed reaches might be declared unfit for drinking. WQI is a critical parameter for assessing the suitability of water for human and ecological use, especially in areas influenced by hydropower development.

In this context, a study presented in [3] emphasizes that groundwater quality in the region has deteriorated to a level that requires treatment before consumption and proactive measures to prevent contamination from both geogenic and anthropogenic sources. These findings underscore the need for environmentally responsible energy solutions such as RoR hydropower which aim to minimize disruption to natural water systems while addressing energy demands. River low-flow conditions, which are frequently brought on by protracted droughts brought on by less precipitation, are becoming more frequent and are problematic for ecosystem stability and water availability. Hydropower reservoirs have been successfully utilized to alleviate these low-flow times, as evidenced by research conducted on Norway's Glomma River presented in [4]. Despite being the biggest source of renewable energy worldwide, hydropower frequently results in serious ecological disruptions. Environmental flows, which are required to safeguard downstream ecosystems, are usually discharged without energy recovery, according to a U.S. based research. Researchers who examined more than 200 hydropower plants discovered that increasing 730 MW of capacity and generating up to 1.8 TWh of electricity annually might be achieved by installing tiny turbines to capture these flows [5]. These results demonstrate how enhancing current infrastructure may raise energy generation without building new dams, promoting the development of more sustainable

Manuscript received April 18, 2026; revised June 23, 2026; accepted July 23, 2026.

[1] Ph.D. Graduate, Graduate School of Engineering Science and Technology, National Yunlin University of Science and Technology.

[2] Assistant Professor, Department of Electrical Engineering, COMSATS University Islamabad Attock Campus, Pakistan.

[3*] Associate Professor (corresponding author), Graduate School of Intelligent Data Science, National Yunlin University of Science and Technology, Taiwan, R.O.C. (E-MAIL: chaudni@yuntech.edu.tw)

energy systems. According to a thorough analysis presented in [6], RoR hydropower systems are becoming more and more popular due to their affordability and reduced environmental impact when compared to conventional dams; nonetheless, their functionality is heavily reliant on technical design criteria. In order to determine the best RoR design for grid-connected and microgrid systems, the study evaluates several modeling techniques for figuring out penstock size, turbine positioning, and energy production.

A thorough grasp of the mechanical principles regulating water motion, particularly KE and PE, is necessary to harness the inherent energy of flowing water. These two energy sources are crucial in establishing the feasibility and efficiency of electricity generation in RoR hydropower systems. RoR systems, in contrast to traditional huge dams, use the river's elevation decrease and flow velocity without storing a lot of energy, hence accurate energy calculation is crucial. Through turbines, the kinetic energy from the water's flow velocity and the potential energy from its height are transformed into mechanical energy, which is subsequently transformed into electrical energy by generators. In [7], a micro hydro power plant (MHPP) prototype model for tiny water discharges, the MHPP waterwheel and the "converters" MHPP speed converters from the waterwheel to the dynamos is presented, thus highlighting the water resources utilization for sustainable energy.

A study on Indonesia's decarbonization goals presented in [8] updates RoR hydro maps through a unique approach that incorporates head, river discharge, gravity, and system efficiency. According to [9], one of the primary causes of the worldwide reduction in freshwater biodiversity is thought to be dam-induced impoundments, which frequently result in notable alterations to the physical, chemical, geomorphological, and hydrological features of rivers. Although RoR systems are most ecofriendly and have no effect on water quality, these changes by river storage negatively influence aquatic ecosystems. The study presented in [10] shows how thirteen tiny RoR hydropower projects in Nepal affected the ecosystem both before and after they were put in place. In addition to offering a clean water source for agricultural fields, the landscape areas for a few chosen hydroelectric projects were obtained using a digital elevation model and superimposed on satellite images from 2013 and 2019. The effects of RoR dams on reservoirs in the tropical South American regions are examined and reported in [11]. Yellow-spotted river turtle nesting areas were monitored as an indicator of dry season river level changes following RoR dam reservoir filling, thus providing a solution for continuous water supply to aquatic life. According to research published in [12], it is proposed that integrating downstream bypass systems with fish guiding structures at RoR locations is a potential mitigating method. In addition to highlighting the significance of hydraulic modeling for ecological performance, the results offer guidance for optimizing RoR design in order to strike a balance between energy generation and the preservation of aquatic habitat. Small RoR water flows may serve as natural water filters by controlling flow and promoting the growth of benthic diatom populations, which improve water self-purification processes, according to recent research published in [13]. RoR systems, as opposite to vast reservoirs, generate clean power with no disturbance to water quality while preserving biological continuity.

Using turbines and generators, hydroelectric facilities transform the mechanical energy of flowing water into electrical energy. A sustainable type of hydropower, RoR use a river's natural flow to provide energy without the need for massive dams or reservoirs. RoR systems are economical, environmentally beneficial, and perfect for off-grid or rural locations where a steady source of electricity is needed. They use fundamental ideas from classical mechanics to capture the KE and PE of water. The current work in [14] attempts to illustrate various components of small hydropower generation in uneven terrains, including site appraisal, development and characteristics, the role of micro-hydro in sustainable development, and related aspects. The hybrid pumped storage-wind-photovoltaic system's complementing functioning at various time scales is examined in [15], which also assesses the system's energy efficiency and financial advantages. A thorough literature assessment on the operation and maintenance aspects of hydropower plants has been published in [16]. The Gómes model was used in [17] to estimate and include the uncertainty of the water inflow status and power price for this producer. A novel coordination mechanism for a large-scale hybrid energy system comprising wind, solar, and cascade hydropower facilities is established in [18]. The overall forecast errors of power output for wind and solar facilities are modeled using scenario analysis based on Latin hypercube sampling and k-means. The primary goal of [19] is to give a thorough review of the potential effects that hydropower operations may have on several facets of the fluvial environment by altering the natural flow regime.

This study presented in [20], is the first to incorporate variable-efficiency turbines into a framework for designing hydropower plants that takes into consideration deep uncertainty in socio-economic and climatic factors in addition to design optimization. In Mediterranean mountainous regions where rainfall is the primary source of uncertainty in river flows, the technique presented in [21] provides a straightforward and practical means of evaluating operational uncertainty in RoR plants. One of the first comprehensive, simulation-based studies on the effects of climate change on Alpine RoR hydel power generation is presented in [22]. This study also considers the implications of technological advancement potential and environmental flow requirements. In order to improve the overall efficiency of the plant, this study [23] suggests an innovative way to replace the single-pond model with a three-pond model. A three-tank nonlinear hydraulic system with the same volume of water as a traditional single pond is the basis for the three-pond concept. This study [24] develops a probabilistic model using neural networks and the Weibull distribution. Seasonal patterns of high and low water flow are estimated using the suggested probabilistic model. The simulation of runoff hydropower generation based on climatic factors at the European level is the focus of this work [25]. Power systems with growing proportions of solar and wind power will be significantly impacted by a better understanding of future RoR generation trends. Compared to solar or wind, RoR plants are less erratic; yet, they are also less deployable than dams with storage capacity.

Given below are the prime objectives of this study:

- To illustrate how RoR is designed and optimized for sustainable energy generation using the principles of classical physics.
- To assess the environmental advantages of RoR over conventional hydropower plants in terms of efficiency and environmental sustainability.
- To investigate how RoR may be incorporated into contemporary electrical engineering systems, such as grid interface and power electronics.
- Help improve comprehension of RoR mechanisms and their practical applications with classical mechanics by using visual aids such as flowcharts, tables, and diagrams for better planning and decision making in water-energy systems.

Theoretical foundation of classical mechanics, which focuses on KE and PE principles, is covered in Section 2. Electrical engineering aspects of RoR are covered in Section 3. The socio-economic and environmental effects are covered in Section 4. A

case study from Northern Pakistan is presented in Section 5. The conclusion is given in Section 6, and the future recommendations are described in Section 7.

2. THEORETICAL FOUNDATION: CLASSICAL MECHANICS

Sir Isaac Newton's revolutionary work in the 17th century gave rise to the fundamental field of physics known as classical mechanics. It offers a methodical framework for examining how objects move under the influence of applied force [26-28]. A large portion of contemporary engineering, particularly in mechanical systems, civil constructions, and energy conversion technologies, is based on classical mechanics, which is largely governed by Newton's three laws of motion and the law of universal gravitation.

Fundamentally, we can describe and forecast the behavior of physical systems, such as turbine blades and planetary orbits. KE and PE are the two main types of mechanical energies that are essential in this context. A strong theoretical foundation for comprehending and simulating energy dynamics in hydropower systems is provided by the combination of Newton's principles of motion and the conservation of mechanical energy. Classical equations of motion and energy transformation may be used to quantitatively characterize the dynamic interaction of water flow with designed components like penstocks and turbines in RoR.

Accurate performance forecasts are made possible by this mechanistic insight, which also helps with system efficiency optimization, turbine type selection, and structural reliability assurance. The whole energy transformation process within an RoR, from the natural river source to the end-user electrical consumption, is depicted in the flowchart. The fundamental idea of energy conservation in RoR operation is illustrated by the energy transformation flowchart in Figure 1,which describes the sequential conversion of natural hydraulic energy both KE and PE into mechanical and subsequently electrical energy.




Fig. 1 Energy transformation flowchart in a RoR

2.1 Potential Energy in River Water

The energy that a body possesses because of its position within the gravitational field is known as PE. The elevation (head) differential between the turbine site and the water intake is the source of PE in RoR. When building systems with a drop in water level, this gravitational energy is a key factor. It is written as follows for objects close to the earth's surface;

$$P.E = mgh. \tag{1}$$

In Eq. (2), m is the mass in kg, g is the gravitational acceleration which is contant at 9.8 m/s^2, h is the height above a reference point in meters.

In run-of-river systems, m is proportional to flow rate (Q) over a time interval (Δt).

$$m = pQ\Delta t. \tag{2}$$

Substituting Eq. (2) in Eq. (1) gives;

$$P.E = pgQH\Delta t. \tag{3}$$

where P is water density (kg/m^3) and Q is discharge (m^3/s). This formulation explicitly connects potential energy to hydrological variables, allowing realistic estimation of instantaneous and cumulative energy available at the site.

Key considerations that should be focused for garbing maximum efficiency from head (P.E) are

- In order to reduce losses and effectively provide water to the turbine, pen-stock size is essential.
- Fore-bays, intake channels, and weirs are examples of civil engineering constructions intended to keep the head under control.
- The main metric used in turbine selection and power estimate is net head or effective head after considering friction losses.

2.2 Kinetic Energy in Flowing Water

The energy that a body possesses as a result of motion is called KE. The water's flow velocity is the source of KE in RoR. Particularly under low head conditions, the significant motion based energy carried by gravity driven water movement downstream can be harnessed by hydro turbines like Kaplan or Cross-flow turbines. In terms of mathematics, it is provided by

$$K.E = \frac{1}{2}mv^2. \tag{4}$$

In Eq. (4), m is denoting the mass of water in kg and v is denoting its velocity in m/s.

For flowing water in a river we have

$$K.E = \frac{1}{2}pQ\Delta tv^2. \tag{5}$$

where v is the mean flow velocity. Unlike static potential energy, K.E depends on river hydraulics, including cross-sectional geometry, flow regime (laminar or turbulent), and velocity distribution. For open-channel flows, the velocity can be approximated using the Manning equation given in Eq. (6) as

$$v = \frac{1}{n}R^{\frac{2}{3}}S^{\frac{1}{2}}. \tag{6}$$

where:
- R= hydraulic radius (m)
- S= channel slope
- n= Manning roughness coefficient

This allows the kinetic energy to be expressed as a function of measurable channel properties, bridging classical mechanics and river hydraulics. This type of energy is obtained directly from the water's flow velocity in RoR. Hydro turbines can use the substantial KE of swiftly flowing water to generate power. Following are some key considerations while using KE for power generation

- Power generation is directly impacted by flow velocity v. A slight increase in velocity greatly increases energy, as per Eq. (4).
- To enhance energy extraction, turbine blade design is tailored to the water flow profile.
- The dynamics of open channel flow are examined through the use of conservation of momentum and fluid mechanics concepts.

This is equivalent to the elevation differential or head between the turbine and the water intake point in RoR. Significant PE may be produced by very little variations in river gradient height. Figure 2 depicts the basic description of KE and PE dynamics, encapsulating their crucial functions in energy transformation.




Fig. 2 Pictorial illustration of KE and PE

2.3 Total Mechanical Energy and Turbine Conversion

Since RoR depend on the elevation and natural motion of river water to generate electricity, they are heavily reliant on the core ideas of PE and KE. The mechanical energy present at the turbine inlet, which is subsequently transformed into electrical energy via a generator, is a result of both types of energy. A chain based on classical mechanics [29-30] governs the transformation of this mechanical energy (KE + PE) into electrical energy in RoR is represented mathematically as

$$Total\ Mechanical\ Energy = K.E + P.E, \tag{7}$$

The total mechanical energy per unit mass of river water combines potential and kinetic contributions as below

$$E_{total} = gH + \frac{1}{2}v^2. \tag{8}$$

In hydro-power systems, the turbine converts a fraction η of this mechanical energy into electrical energy as represented below

$$P = \eta pQ(gH + \frac{1}{2}v^2). \tag{9}$$

Here, η is turbine-generator efficiency, which depends on turbine type, flow conditions, and design operating point. For example Kaplan turbines are suited for low-head, high-flow rivers with efficiency ~90% and Pelton turbines are suitable for high-head, low-flow sites.

By integrating P over the operational time and considering seasonal flow variability, annual energy production can be estimated, providing a direct link between classical mechanics and practical hydro-power output.

The hydro turbine uses all of this total mechanical energy to turn a generator, which generates electricity. A thorough grasp of classical mechanics is necessary to balance turbine characteristics, head, and flow rate in order to optimize this process. Figure 3 shows hydro turbine coupled to a generator in an RoR using both PE from an elevation difference and KE from flowing water to generate electricity.




Fig. 3 Diagram showing how KE and PE are converted into electrical energy in an RoR.

2.4 Incorporation of Advanced Hydrodynamics

To address spatial and temporal variability in real rivers:

Bernoulli's equation is used to relate velocity head, pressure head, and elevation head along streamlines as given in below

$$\frac{v^2}{2} + gz + \frac{\mathrm{P}}{\rho} = constant. \tag{10}$$

where;
- v= flow velocity (m/s)
- g= gravitational acceleration (9.8m/s^2)
- z= elevation head relative to a refrence datum (m)
- P= pressure of the flowing fluid (Pa)
- ρ= density of water (kg/m^3)

In hydropower applications, the three terms used above representing velocity head, pressure head, and elevation head respectively, defines total hydraulic head available in the system.

However, in real hydraulic systems the available head is reduced due to frictional and turbulence related energy losses occurring in penstocks, channels, and other hydraulic components. These losses are commonly represented as head losses (h_f). The effective head i.e. $H_{effective}$ obtained after the head losses due to

friction and turbulence are considered using Darcy–Weisbach or Chezy–Manning formulas as below

$$H_{effective} = H - h_f . \tag{11}$$

Also H is the gross hydraulic head between upstream and downstream water levels in (m). Turbine-specific power curves can then be applied to predict instantaneous efficiency based on flow rate Q and net head $H_{effective}$.

The frictional head loss (h_f) can be estimated using the Darcy-Weisbach equation

$$h_f = f \frac{Lv^2}{D2g}. \tag{12}$$

where:
- f= Darcy friction factor (Dimensionless)
- L= length of the length of the conduit or penstock (m)
- D= hydraulic diameter of the conduit (m)
- v= average flow velocity (m/s)

3. ELECTRICAL ENGINEERING ASPECTS

For efficient energy conversion, control, transmission, and use, RoR not only relies on the physical behavior of water as determined by classical mechanics, but also on strong electrical engineering concepts. One of the primary purposes of electrical machines, particularly alternators or generators, is to perform effectively under the changing load conditions typical of RoR systems. These machines convert the mechanical energy produced by turbine movement into electrical energy.

3.1 Turbine Generator Pairing

The most suitable turbine-generator coupling in RoR is determined by the hydraulic head, flow rate, and required power output, all of which are closely related to the turbine selection. To guarantee system stability and efficiency, electrical generators must be synchronized in terms of electrical output characteristics in addition to mechanical coupling and speed.

In hydropower applications, specification of three main turbines are often employed, each of which is appropriate for a variety of operating environments is presented in Table 1[31-32].

Table 1 Comparison of Kaplan, Francis, and Pelton turbines for optimal turbine generator pairing

Turbine	Suitable Head (m)	Flow Rate (m^3/s)	Efficiency (%)
Kaplan	2-20	High	85-90
Francis	10-300	Medium	90-95
Pelton	>300	Low	85-90

Kaplan turbines are appropriate for rivers with mild slopes because they are perfect for RoR installations with low head and high flow. Dynamic efficiency optimization is made possible by their movable blades. Francis turbines are adaptable and appropriate for settings with medium head and moderate flow. Both RoR and storage based hydropower plants make extensive use of them. Pelton turbines work best in environments with high head and low flow, which are usually found in hilly areas. They work by using high velocity jets to transform PE into KE. The schematic diagram of a turbine generator pairing is presented in Figure 4.




Fig. 4 Schematic diagram of turbine generator pairing in a RoR

3.2 Generator Operation and Selection

Depending on the system size and grid connectivity, synchronous or asynchronous generators are frequently employed in RoR. These generators need to be properly chosen using factors like:
- Head and flow rate (which impact power generation).
- Turbine's rotational speed.
- Requirements for frequency (50/60 Hz).
- The ability to synchronize with the grid.

According to Faraday's Law, generators use electromagnetic induction to transform the mechanical rotational energy of turbines into alternating current (AC) electrical energy.

3.3 Power Conditioning and Voltage Regulation

After generation, electricity typically needs to be synchronised to meet local consumption or transmission requirements. This includes:
- When there is variable frequency generation, rectifiers and inverters are used.
- Transformers are used to step down voltage for local distribution and step up voltage for long distance transmission.
- Automatic load controllers and voltage regulators are used to keep the system stable.

3.4 Grid Integration and Synchronization

Synchronization is essential for RoR systems that are linked to the national grid. Before connecting, electrical engineers must make sure that the generated power's voltage, frequency, and phase angle fit the grid's specifications. This might entail:

- Correction of power factor.
- Phase locked loops.
- Relays for protection against damage or back feeding during malfunctions.

3.5 Monitoring, Control, and SCADA Systems

Microcontroller based digital control units and Supervisory Control and Data Acquisition (SCADA) systems are integrated in contemporary RoR installations to:

- Keep an eye on the generator output, head, turbine speed, and flow rate.
- Automatically modify load levels or gate openings.
- Identify and address issues or variations in the supply of water.

3.6 Electrical Load Management

In order to maximize performance, load management measures are used since RoR may be susceptible to seasonal or diurnal flow fluctuation. These consist of:

- Systems for storing batteries for load balancing and peak shaving.
- To deal with surplus generation, dump loads.
- Demand side management used to match supply and demand.

The integration of electrical components is essential to the effective and dependable generation and distribution of electricity in a RoR. Every part, from the generator to the load controller, has a distinct role in preserving electrical performance, protection, and control, as indicated in Table 2. For example, transformers control voltage levels for safe transmission, and the generator transforms the mechanical output of the turbine into electrical power. The AC/DC flow is controlled by inverters and converters, and real time monitoring is made possible via SCADA systems. System stability and operational safety are guaranteed by extra components such as load controllers and protective relays.

Table 2 Electrical Components and Their Functions in RoR

Component	Function
Generator	Changes mechanical energy into electrical energy.
Transformer	Steps up and down voltage levels for transmission and distribution.
Inverter/Converter	Regulates frequency and converts AC/DC as essential.
SCADA System	Real time observing and control.
Protection Relays	Prevents faults and overloads.
Load Controller	Balances generation and demand.

4. ENVIRONMENTAL AND SOCIOECONOMIC IMPACT

By using the KE and PE of flowing water without need for enormous reservoirs or significant structural changes, RoR provides a sustainable and flexible alternative to traditional hydropower systems that generates electricity with a comparatively minimal effect. This design offers significant advantages to human groups, especially in rural and isolated areas, while minimizing disturbance to ecosystems.

4.1 Environmental Impact

RoR's design features, which eliminate the need for significant damming or land flooding, make it an environmentally favorable option. Methane emissions from submerged plants, habitat damage, and changes to the natural water cycle are all greatly decreased as a result.

4.1.1 Biodiversity Preservation

The preservation of both terrestrial and aquatic biodiversity is one of RoR's main benefits. Riverine ecosystems and fish migration are unaffected since the water flow remains mainly unhindered. Additionally, the lack of big dams prevents habitat fragmentation and permits organic flow of nutrients and sediments.

4.1.2 Water Quality and Flow Regulation

By maintaining river's natural flow regime, RoR protects the purity of the water. RoR guarantees continuous water circulation, which is essential for aquatic health, in contrast to conventional hydropower dams, which might result in thermal stratification or standstill. This raises dissolved oxygen levels and lowers the chance of algae blooms.

4.1.3 Carbon Footprint and Climate Impact

RoR significantly lowers the carbon footprint by removing emissions linked to extensive building projects, reservoir maintenance, and vegetation deterioration, even though hydroelectric power is already a low-carbon energy source. Small scale hydropower systems like RoR release less than 15 g CO_2/kWh, while coal based systems emit more than 500 g CO_2/kWh, according to the International Energy Agency (IEA) (IEA, 2022) [33].

The average carbon dioxide (CO_2) emissions per kWh for several energy generating sources are shown in Figure 5. Significantly lower than conventional fossil fuel based sources like coal and natural gas, RoR have some of the lowest emission levels, on par with wind energy. This demonstrates that RoR is an environmentally friendly option for producing power, especially in places that want to lessen their carbon impact.

The National Renewable Energy Laboratory (NREL, 2020), the Intergovernmental Panel on Climate Change (IPCC, 2021), and the International Energy Agency (IEA, 2022) are among the reliable sources from which the emission numbers are obtained [34-37].




Fig. 5 CO_2 Emission per KWh by Energy Sources

4.2 Socioeconomic Impact

RoR initiatives provide major social benefits in addition to environmental ones, especially in areas with poor access to power. They are perfect for localized energy independence and rural electrification because of their modular and decentralized design.

4.2.1 Community Empowerment and Local Employment

RoR installations can be owned and run by the community, providing jobs while they are being built, run, and maintained. Local worker participation lowers project costs and improves engineering, project management, and electrical system skill development.

4.2.2 Rural Electrification and Quality of Life

The quality of life in off-grid settlements is enhanced by RoR, which offers a reliable and sustainable power supply. Improved education, healthcare, and economic growth are all directly impacted by the growth of schools, clinics, communication networks, and small businesses.

4.2.3 Economic Viability and Cost Savings

When compared to microgrids that rely on fossil fuels, RoR systems are often less expensive over the course of their lifetime. Because they don't require fuel or large moving components, they have low operational expenses once installed. There are significant financial benefits in the form of lower energy costs, increased agricultural output (such as through irrigation powered by solar or hydropower), and new business prospects. Some major contibutions of RoR are tabulated in Table 3 for Rural Community.

Table 3 RoR's socioeconomic advantages in rural community

Impact Area	RoR Contibution
Employment	Generation of local jobs in maintenance and construction.
Education	Internet connectivity, digital instructional resources, and lights are all made possible by electricity.
Healthcare	Power for emergency illumination, diagnostic devices, and refrigeration.
Agriculture	Supports agro processing facilities and irrigation systems.
Communication	Permits internet access and mobile network functioning.
Gender Equality	Lessens household chores (like gathering firewood), allowing women to pursue education.

4.3 Challenges, Limitations and Mitigation Strategies

Notwithstanding RoR's encouraging promise, a number of obstacles prevent its best use. Seasonal and climatic variations in water flow can cause irregular power generation, which compromises grid stability. Furthermore, rigorous technical and environmental design are needed to address site specific restrictions including topography, sedimentation, and biological limits. Concerns about integration with current electrical infrastructure, maintenance in distant locations, and turbine performance at low flows are other persistent technical challenges.

Smart grid solutions, adaptive flow control technologies, and hybrid energy systems such as integrating RoR with solar or battery storage are being investigated more and more in an effort to address these issues. Sustainable development and the long-term acceptance of such projects may also be ensured by routine environmental reviews and community involvement.

5. CASE STUDY: RUN-OF-RIVER HYDROPOWER IMPLEMENTATION IN NORTHERN PAKISTAN

Located in northern Pakistan's Hindu Kush Mountains, the Chitral district is distinguished by its untamed landscape and rivers that are fed by glaciers. The area is perfect for RoR because of these rivers' significant potential for RoR hydropower plants. One promising location for such improvements has been found to be the Lutkho River.

5.1 The Chitral Hydropower Project

Located on the right bank of the Lutkho river, the Chitral hydropower plant was first put into service in June 1975 and had a 1 MW capacity. Its capacity is planned to be increased to 5 MW in recognition of the region's increasing energy demands [38]. Utilizing a flow rate of around 27 m^3/s and operating with a net head of about 270 meters, the updated plant uses the Lutkho river's KE and PE to produce power.

5.2. Technical Specifications

By using a RoR system, the upgraded Chitral hydropower plant reduces its environmental effect and does away with the need for enormous reservoirs. A diversion weir, a headrace channel, a fore bay, penstocks, and a powerhouse with turbines and generators appropriate for the hydraulic characteristics of the site are all features of the plant's design. Some major technical specifications of Chitral hydropower plant are described in Table 4.

Table 4 Technical Specifications of the Chitral Hydropower Plant

Parameter	Specification
Installed Capacity	1 MW (Planned: 5 MW)
Net Head	~269-280 meters (estimated)
Design Flow Rate	~27 m^3/s (estimated)
Turbine Type	Francis
Generator Type	Synchronous AC
Operational Since	1975 updated in 2020

5.3 Environmental and Socioeconomic Impact

There have been notable social and environmental advantages to Chitral's adoption of the RoR:

The main environmental benefits of this project are:

- Decreased greenhouse gas emissions as a result of less dependence on fossil fuels.
- Minimal ecological disruption due to the RoR design.

Some important socioeconomic benefits are listed below;

- Supplying local populations with dependable power, improving their standard of living.
- Boosting regional companies and industries by providing better access to electricity.
- Creation of jobs during the periods of building and operation.

According to research presented in [39], rural communities in northern Pakistan have been changed by micro hydropower projects that have improved educational outcomes, enabled the use of domestic equipment, and provided electricity.

5.4 Challenges and Mitigation Strategies

Based on the extreme remote location and tough weather and high mountain ranges, Notwithstanding the achievements, the project encountered a number of difficulties. Some main difficulties and their mitigation strategies are tabulated below in Table 5.

Table 5 Main challenges and mitigation strategies of Chitral Hydropower Plant

Challenge Type	Challenge	Mitigation Strategy
Seasonal Variability	Seasonal variations in glacial meltwater flow impact the reliability of electricity generation.	Mitigation strategies include integrating other renewable energy sources and putting flow regulating measures into place.
Technical Constraints	Transportation and maintenance of the equipment were logistically complicated by the remote location.	Using modular equipment and providing local staff with operations and maintenance training.
Environmental Concerns	Possible effects of water diversion on aquatic ecosystems.	Evaluations of environmental flow to make sure there is enough water in the river to support ecosystems.

The basic parts of the Chitral hydropower plant, a RoR that uses rivers fed by glaciers in northern Pakistan, are depicted in the schematic Figure 6. The operational cycle from water diversion to energy generation is clearly shown. To guarantee a constant water flow into the penstocks, water is sent via a headrace canal from the diversion weir to a forebay tank. KE and PE are transformed into mechanical energy by the penstocks, which guide the high-pressure water to the powerhouse's turbine. A linked generator is then used to convert this energy into electrical power. The cycle is eventually completed when the tailrace returns the used water to the river.

This design ensures energy generation while causing the least amount of environmental disturbance possible and maintaining the river's natural path. It also makes it easier to see how RoR designs are small and effective in harsh, isolated areas.




Fig. 6 Schematic Diagram of the Chitral Hydropower Plant

6. CONCLUSION

The deep connection between basic physics and practical engineering is demonstrated by the incorporation of classical mechanics, namely the concepts of KE and PE, into the architecture and functioning of RoR. In physically varied areas like northern Pakistan, RoR serves as an example of how sustainable energy solutions may be successfully implemented. These technologies ensure dependable power generation while minimizing ecological disturbance by utilizing natural water flows without the need for large reservoirs. Advanced electrical components, automation, and theoretical understanding of energy transformation highlight RoR's multidisciplinary character, spanning from engineering and physics to the social and environmental sciences. Furthermore, the Chitral case study demonstrates the socioeconomic improvement that such systems provide in isolated areas in addition to their technological feasibility. The RoR concept is a shining example of sustainable and contextually aware development as the world's energy demands grow. Following are the key takeaway points listed below

- By using gravity fed water systems to transform KE and PE into electrical power, RoR makes use of classical mechanics.
- These systems are perfect for ecologically sensitive areas since they have less impact on the environment than traditional large-scale hydropower.
- From turbines to SCADA systems, RoR components exhibit a high level of technical integration, improving dependability and efficiency.
- With year-round performance, the Chitral case study illustrates the feasibility of RoR in high-altitude, glacier fed locations.
- A multifaceted solution, RoR offers social advantages such local jobs, energy availability, and lower carbon emissions.
- Because of their adaptability and scalability, RoR models provide a blueprint for sustainable development in comparable en-

vironments around the globe.

7. FUTURE RECOMMENDATIONS

The foundation of engineering and technology is still classical mechanics. Its ideas support the design and optimization of systems that transform natural forces into useful energy, such as RoR, in addition to aiding in the explanation of natural events. Engineers can create greener and more sustainable power solutions by efficiently using KE and PE. The following next directions are suggested in order to optimize the potential of RoR and promote their broad adoption:

- Multi physics Modeling and Simulation: To maximize RoR performance from a physics-based design standpoint, future research should use sophisticated simulation tools that combine fluid dynamics, structural mechanics, and electromagnetic analysis.
- Hybrid Energy Integration: Particularly in isolated or off-grid areas, RoR can be combined with other renewable energy sources like solar or wind to provide a more reliable and regular energy supply.
- Implementation of the Smart Grid and IoT: RoR can improve efficiency, fault detection, and adaptive load management when integrated into smart grid frameworks and supplemented by real-time monitoring via IoT devices.
- Financial and Policy Incentives: Government assistance in the form of microfinance, feed-in tariffs, and subsidies can hasten the development of RoR, particularly in rural and impoverished areas.
- Community Based Ownership Models: Promoting sustainable energy access and socioeconomic empowerment may be achieved by enlisting the help of local communities in the operation and ownership of RoR.
- Environmental Impact Studies: To continually assess and reduce the ecological imprint of RoR installations, long-term, site-specific studies should be carried out.
- Educational Integration: To encourage students' research and progress, RoR should be included as a case study in university-level physics and engineering curricula.

Data Availability Statement

The data supporting the findings of this study are derived from publicly available sources cited throughout the manuscript. No new datasets were generated during the current study.

Conflict of Interest

All authors declare no conflict of interest.

REFERENCES

[1] Arai, Ryosuke, Yasushi Toyoda, and So Kazama. "Streamflow maps for run-of-river hydropower developments in Japan." *Journal of Hydrology* 607 (2022): 127512.

[2] Sofi, M. S., Hamid, A., Bhat, S. U., Rashid, I., & Kuniyal, J. C. (2022). "Impact evaluation of the run-of-river hydropower projects on the water quality dynamics of the Sindh River in the Northwestern Himalayas." *Environmental Monitoring and Assessment,* **194**(9), 626.

[3] Ram, A., Tiwari, S. K., Pandey, H. K., Chaurasia, A. K., Singh, S., & Singh, Y. V. (2021). "Groundwater quality assessment using water quality index (WQI) under GIS framework." *Applied Water Science*, **11**, 1-20.

[4] Olabiwonnu, F. O., Bakken, T. H., & Anthony Jr, B. (2022). "Achieving sustainable low flow using hydropower reservoir for ecological water management in Glomma River Norway." *Sustainable Water Resources Management,* **8**(2), 53.

[5] Garrett, K. P., McManamay, R. A., & Witt, A. (2023). "Harnessing the power of environmental flows: Sustaining river ecosystem integrity while increasing energy potential at hydropower dams." *Renewable and sustainable energy reviews,* **173**, 113049.

[6] Tsuanyo, D., Amougou, B., Aziz, A., Nka Nnomo, B., Fioriti, D., & Kenfack, J. (2023). "Design models for small run-of-river hydropower plants: a review." *Sustainable Energy Research,* **10**(1), 3.

[7] Suryatna, B. S., & Agustina, T. (2021, March). "Prototype design of waterwheel micro hydro power plants for small water discharge." *In IOP Conference Series: Earth and Environmental Science* (Vol. **700**, No. 1, p. 012032). IOP Publishing.

[8] Pranoto, B., Soekarno, H., Cendrawati, D. G., Akrom, I. F., Irsyad, M. I. A., Hesty, N. W., ... & Aman, M. (2021, November). "Indonesian hydro energy potential map with run-off river system." *In IOP Conference Series: Earth and Environmental Science* (Vol. **926**, No. 1, p. 012003). IOP Publishing.

[9] Ticiani, D., Larentis, C., de Carvalho, D. R., Ribeiro, A. C., & Delariva, R. L. (2023). "Dam cascade in run-of-river systems promotes homogenisation of fish functional traits in a plateau river." *Ecology of Freshwater Fish,* **32**(1), 147-165.

[10] Neupane, S., Das, B., Velvizhi, G., Neupane, S., & Pradhan, P. M. (2023). "Impact of thirteen run-of-river hydroelectric projects on land use land cover and ecosystem services in Nepal." *International Journal of Energy and Water Resources,* **7**(4), 513-533.

[11] Bárcenas-García, A., Michalski, F., Gibbs, J. P., & Norris, D. (2022). "Amazonian run-of-river dam reservoir impacts underestimated: Evidence from a before–after control–impact study of freshwater turtle nesting areas." *Aquatic Conservation: Marine and Freshwater Ecosystems,* **32**(3), 508-522.

[12] Zöschg, H., Dobler, W., Aufleger, M., & Zeiringer, B. (2023). "Evaluation of hydraulics and downstream fish migration at run-of-river hydropower plants with horizontal bar rack bypass systems by using CFD." *Water,* **15**(6), 1042.

[13] Wang, Y., Wu, N., Tang, T., Wang, Y., & Cai, Q. (2022). "Small run-of-river hydropower dams and associated water regulation filter benthic diatom traits and affect functional diversity." *Science of the Total Environment,* **813**, 152566.

[14] Karre, R. K., Srinivas, K., Mannan, K., Prashanth, B., & Prasad, C. R. (2022, May). "A review on hydro power plants and turbines." *In AIP Conference Proceedings* (Vol. **2418**, No. 1). AIP Publishing.

[15] Wang, Z., Fang, G., Wen, X., Tan, Q., Zhang, P., & Liu, Z. (2023). "Coordinated operation of conventional hydropower plants as hybrid pumped storage hydropower with wind and photovoltaic plants." *Energy Conversion and Management,* **277**, 116654.

[16] Kumar, K., & Saini, R. P. (2022). "A review on operation and maintenance of hydropower plants." *Sustainable Energy Tech-*

nologies and Assessments, **49**, 101704.

[17] Daneshgar, S., & Zahedi, R. (2022). "Investigating the hydropower plants production and profitability using system dynamics approach." *Journal of Energy Storage,* **46**, 103919.

[18] Lu, L., Yuan, W., Su, C., Wang, P., Cheng, C., Yan, D., & Wu, Z. (2021). "Optimization model for the short-term joint operation of a grid-connected wind-photovoltaic-hydro hybrid energy system with cascade hydropower plants." *Energy Conversion and Management,* **236**, 114055.

[19] Kuriqi, A., Pinheiro, A. N., Sordo-Ward, A., Bejarano, M. D., & Garrote, L. (2021). "Ecological impacts of run-of-river hydropower plants—Current status and future prospects on the brink of energy transition." *Renewable and Sustainable Energy Reviews,* **142**, 110833.

[20] Yildiz, V., Brown, S., & Rougé, C. (2024). "Importance of variable turbine efficiency in run-of-river hydropower design under deep uncertainty." *Water Resources Research,* **60**(6), e2023WR035713.

[21] Gómez-Beas, R., Contreras, E., Polo, M. J., & Aguilar, C. (2024). "Stochastic flow analysis for optimization of the operationality in run-of-river hydroelectric plants in mountain areas." *Energies,* **17**(7), 1705.

[22] Tobias, W., Manfred, S., Klaus, J., Massimiliano, Z., & Bettina, S. (2023). "The future of Alpine Run-of-River hydropower production: climate change, environmental flow requirements, and technical production potential." *Science of the Total Environment,* **890**, 163934.

[23] Saeed, A., Shahzad, E., Khan, A. U., Waseem, A., Iqbal, M., Ullah, K., & Aslam, S. (2023). "Three-Pond Model with Fuzzy Inference System-Based Water Level Regulation Scheme for Run-of-River Hydropower Plant." *Energies,* **16**(6), 2678.

[24] Afzaal, M. U., Khan, M. H., & Elahi, A. (2022, June). "Water flow patterns generation model for grid connected run-of-river hydro power plant." *In 2022 IEEE International Conference on Environment and Electrical Engineering and 2022 IEEE Industrial and Commercial Power Systems Europe* (EEEIC/I&CPS Europe) (pp. 1-6). IEEE.

[25] Sessa, V., Assoumou, E., Bossy, M., & Simões, S. G. (2021). "Analyzing the applicability of random forest-based models for the forecast of run-of-river hydropower generation." *Clean Technologies,* **3**(4), 858-880.

[26] Halliday, D., Resnick, R., & Walker, J. (2013). "Fundamentals of physics." *John Wiley & Sons.*

[27] Suárez, Á., Martí, A. C., Zuza, K., & Guisasola, J. (2023). "Electromagnetic field presented in introductory physics textbooks and consequences for its teaching." *Physical Review Physics Education Research,* **19**(2), 020113.

[28] Munson, B. R., Young, D. F., & Okiishi, T. H. (2013). "Fundamentals of fluid mechanics (7th ed.)." *Wiley.*

[29] Khan, M. J., & Iqbal, M. T. (2005). "Preliminary design of a run-of-river micro-hydro plant." *Renewable Energy,* **30**(5), 671–682 . https://doi.org/10.1016/j.renene.2004.07.001

[30] U.S. Department of Energy. (2016). "Hydropower vision: A new chapter for America's 1st renewable electricity source. U.S." *Department of Energy.* https://www.energy.gov/eere/water/articles/hydropower-vision-report.

[31] U.S. Department of Energy. (2001). "Hydropower Program: Turbine Selection for Small Hydropower." *Office of Energy Efficiency and Renewable Energy.* https://www.energy.gov/sites/default/files/2014/05/f16/2001_smallhydro_turbine_selection.pdf

[32] Paish, O. (2002). "Small hydro power: Technology and current status." *Renewable and Sustainable Energy Reviews,* **6**(6), 537–556. https://doi.org/10.1016/S1364-0321(02)00006-0

[33] International Energy Agency. (2022). "World Energy Outlook 2022." *OECD Publishing.*

[34] Intergovernmental Panel on Climate Change. (2021). "Climate Change 2021: The Physical Science Basis." *Contribution of Working Group I to the Sixth Assessment Report.*

[35] National Renewable Energy Laboratory. (2020). *Life Cycle Greenhouse Gas Emissions from Electricity Generation.* NREL/TP-6A20-80580.

[36] World Bank. (2019). *Hydropower Sustainability Guidelines on Good International Industry Practice.*

[37] Kumar, A., Schei, T., Ahenkorah, A., Caceres Rodriguez, R., Devernay, J. M., Freitas, M., & Wang, Z. (2011). "Hydropower. *In IPCC Special Report on Renewable Energy Sources and Climate Change Mitigation* (pp. 437–496).

[38] Water and Power Development Authority (WAPDA). (n.d.). Chitral Power Enhancement.

[39] Cheema, A. R. (2016). The "smart villages" of northern Pakistan. *Dialogue Earth.*